

## Introduction

American Innovations (AI) is pleased to announce version 7.2 of our Allegro software. Your Allegro software must be updated to version 7.0 or newer if you intend to use it with PCS version 1.13 or newer.

This document explains how to upgrade the software on an Allegro MX Field PC. If you have any questions or need further assistance, give us a call at 1-800-229-3404 or email us at support@aiworldwide.com.

# Upgrade the Software on the Allegro MX

Perform the steps detailed in *Prepare for the Upgrade* before proceeding with the instructions listed under *Install the Software*.

## Prepare for the Upgrade

Complete the following steps before installing the software:

- 1. Connect the Allegro MX to your computer.
- 2. Sync data on the Allegro with PCS.
- 3. Navigate to the Allegro CAB file (AI-MX-CE5-7-1-2-2018-XX-XX.CAB) on your computer and copy the file to the Allegro MX's SD card (Juniper Systems Allegro > SD card).
- 4. Back up all files on the SD card by copying them to your computer, then delete all files on the SD card.
- 5. Take inventory of any third party software that has been installed on your Allegro MX, such as GPS Controller or screen capture software. You will need to re-install the software at the end of the upgrade process.
- 6. Perform a factory default reset by pressing and holding the On/Off button for 1-2 seconds. Tap Reset and immediately hold down the Alt, Ctrl, and Del buttons simultaneously for at least 8 seconds.







### Figure Upgrade-1. Alt, Ctrl, and Del Buttons

A status bar displays across the lower half of the screen. You can ignore any *Unrecognized Card* message that displays.

- 7. When the reset process has completed, tap the screen to set up the Allegro:
  - a. For screen alignment, tap the center of the cross hairs as they appear on the screen with a stylus.
  - **b.** For the tutorial, tap **Skip**.
  - c. Set time zone, date, and time.
  - d. Tap Next.
  - e. When the Settings screen displays, click OK.

鸄 Se	ttings	<b>;;;                                  </b>					
Power							
● Sar ○ Ful	ne battery, i battery	ues Charge Percentage					
⊖ Chá ⊖ Ent	arge unknow er percentae	Battery Capacity acity					
In-Vehicle Charge Mode							
Battery	Advanced	Processor	Charge Settings				

Figure Upgrade-2. Settings Screen

8. If you see an Unrecognized Card or Unidentified USB Device message, tap Cancel.

### Install the Software

- 1. Connect the Allegro MX to your computer.
- 2. Navigate to the old Allegro CAB file (Juniper Systems Allegro > SD Card). Delete any previous versions of Allegro CAB files in the folder.
- 3. On the Allegro MX, tap Start > File Explorer.



#### Figure Upgrade-3. File Explorer

4. Tap the folder name at the top of the *File Explorer* window to reveal the Show drop-down menu.

🐉 File Explorer	## <b>-</b> 4	<del>(</del> 5:44 🗙
📃 Show 👻		Name 🚽
<u>My</u> Device	12/10/18	23.0K 🔺
• <u>P</u> rogram Files	12/10/18	787K
Storage	12/10/18	584K
Uat um GpsConfig	12/7/18	55.0K
🖉 GpsConfigUblox	12/10/18	199K
🔆 GpsStatus	12/7/18	255K
PS PeriodicSurvey	12/10/18	1.02M
船 Restarter	12/10/18	146K
<sup>RE</sup> G SetDaqRegKeys	12/7/18	8.00K 🖵
Up	 Me	nu

### Figure Upgrade-4. File Explorer - Show Drop-down Menu

- 5. Tap SD Card or Storage from the Show drop-down menu.
- 6. Tap to install the GPS utility software applicable to your Allegro's GPS receiver. For uBlox, install AMXU GPS Pod Setup. For Trimble Lassen GPS receivers, install GPS Pod Setup.
- 7. Ensure Device is selected as the location to install the software and tap Install.

Cancel



l

### Figure Upgrade-5. Install Location

Install

- 8. When the install completes, tap OK.
- 9. Tap the current Allegro CAB file to begin the software installation.
- 10. Tap OK when the *Installation* warning appears. If prompted to choose a location to install the software, ensure **Device** is selected as the location to install the software and tap **Install**.

- 11. Tap **I accept** when the *AI Software License Agreement* displays. The *AI Software License Agreement* is located in the AI folder for review.
- 12. Tap Restart now.

Restart		▶ # 7 € € = :	10:38
The system n	nust be restarted to initi	alize drivers.	
	Restart now	Cancel	
			ОК

Figure Upgrade-6. Restart Screen

- **13.** Reset communication parameters of the Allegro's internal GPS pod (*AMXU GPS Pod Setup* utility for uBlox; *GPS Pod Setup* utility for Trimble). Refer to the Allegro MX User Guide for further instructions.
  - a. Tap Start > Programs > AMXU Pod Setup or GPS Pod Setup.
  - b. Tap Al.
  - c. After the settings are saved, tap OK.

GPSPod	Setup		# <b>* 4</b> € 8:49 🗙			
RMC VTG GGA GGA SBAS/W Enabled	GSV GLL GRS GST AAS	✓ ZDA GBS DTM Sta Set	AI tus: tings Saved.			
Toggle NMEA sentences by tapping the Version: 1.7 check boxes above. (21Nov12)						
OK						

Figure Upgrade-7. GPSPodSetup Screen Reset



- 14. Set GPS baud rate:
  - a. If not on the Programs screen, tap **Start > Programs**.
  - b. Tap Options.
  - c. For uBlox, select **38400** from the Baud field drop down list. Select **9600** for Trimble GPS receivers.
  - d. Tap OK to close the GpsStatus About screen; tap OK to close GpsStatus
- **15.** Review the third party software inventory created during *Prepare for the Upgrade* and install the software as required.
- **16.** Contact Al Support at 1-800-229-3404 or support@aiworldwide.com to determine the next steps to ensure a consistent connection between your Allegro MX and PCS.